



OPTIONAL EXTRAS (NOT SHOWN ON DRAWING)
 EYEBATH FITTED EXTERNALLY
 INTERNAL WALL/CUBICLE HEATER
 LOW/HIGH WATER TEMP
 SPRING LOADED DOORS
 STRIP CURTAINS

TECHNICAL DETAILS
 INLET WATER SUPPLY: REC. 2 - 10 BAR
 FLOW RATE: 75 LPM
 INLET: 1" BSP or NPT
 OUTLET: 2" BSP or NPT
 WEIGHT: 350 - 400 KG

CLASSIFICATION
 ALL ELECTRICS SUITABLE FOR NON HAZARDOUS AREAS

REFERENCE ONLY

NAME	DATE	DIMENSIONS ARE IN MILLIMETRES UNLESS SPECIFIED OTHERWISE	TITLE: 1200 - 1500 TANK SHOWER NON HAZARDOUS	REVISION	A
DRAWN: P.S	07/08/2014			REV DATE:	13/10/2014

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SHOWERS & EYEBATHS SERVICES LTD. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Showers & Eyebaths services LTD IS PROHIBITED.	TOLERANCES: LINEAR: ALL DIMENSIONS ±5mm ANGULAR: ±0.5°	DWG NO.	SE-GA-GFTS15	SCALE:	1:30
				SHEET	1 OF 1




SHOWERS & EYEBATHS
 Showers & Eyebaths Services Ltd.
 Safety House, 23c Sandwash Close, Rainford
 Industrial Estate, Rainford, Lancashire, WA11 8LY U.K.
 Tel + 44 (0) 1744 889677 Fax +44 (0) 1744 885663
 e-mail: sales@safety-showers.com www.safety-showers.com