



**OPTIONAL EXTRAS (NOT SHOWN ON DRAWING)**  
 EYEBATH FITTED EXTERNALLY  
 INTERNAL WALL/CUBICLE HEATER  
 LOW/HIGH WATER TEMP  
 SPRING LOADED DOORS  
 STRIP CURTAINS

**TECHNICAL DETAILS**  
 INLET WATER SUPPLY: REC. 2 - 10 BAR  
 FLOW RATE: 75 LPM  
 INLET: 1" BSP or NPT  
 WEIGHT: 350 - 400 KG

**CLASSIFICATION**  
 ALL ELECTRICS SUITABLE FOR NON HAZARDOUS AREAS

**REFERENCE ONLY**

NAME	DATE	DIMENSIONS ARE IN MILLIMETRES UNLESS SPECIFIED OTHERWISE	TITLE: 1200 - 1500 TANK SHOWER NON HAZARDOUS WITHOUT SUMP WITH CHILLER	REVISION	A
DRAWN: P.S	07/08/2014			REV DATE:	10/10/2014
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SHOWERS & EYEBATHS SERVICES LTD. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Showers & Eyebaths services LTD IS PROHIBITED.		TOLERANCES: LINEAR: ALL DIMENSIONS ±5mm ANGULAR: ±0.5°	DWG NO.	SE-GA-GFTS15-NS-WC	A3
			DO NOT SCALE DRAWING	SCALE:1:35	SHEET 1 OF 1

**SHOWERS & EYEBATHS**  
 Showers & Eyebaths Services Ltd.  
 Safety House, 23c Sandwash Close, Rainford  
 Industrial Estate, Rainford, Lancashire, WA11 8LY U.K.  
 Tel + 44 (0) 1744 889677 Fax +44 (0) 1744 885663  
 e-mail: sales@safety-showers.com www.safety-showers.com

ISO9001  
 WCS  
 Certificate No. 6974