



# SAFETY SHOWERS & EYEBATHS

SHOWERS AND EYEBATHS SERVICES

## GFS1H & GFS3H Trace heated mains fed shower



### Corrosion Resistant Showers



Manufactured from GRP Yellow outer case, ABS pipe work and stainless steel which are corrosion resistant materials, giving superior strength; a long life, and suitability for outside use.

Designed to be highly visible for ease of identification and work first time every time. This unit comes with trace heating around the internal operating valve and pipework and therefore ideal for any environments to -20 deg c.

Available for non hazardous and hazardous areas.

#### KEY FEATURES

- 2-3 bar water supply pressure recommended to give unit 76lpm
  - No risk of Legionella
  - Stainless base plate-304
  - Stainless & ABS internal pipework
  - Internal trace heating wire & insulation
  - Trace heating stat
  - Stainless fittings & Valves
  - 1" BSPF Stainless inlet (flanged inlets available as an option)
  - Stainless panic bar shower operation
  - Stainless testing lever
  - Highly visible robust outer jacket- YELLOW GRP reduces solar gain & physical damage)
  - Rigid Pictorial Safety sign & green & white stripes
  - 3 x Stainless Spray nozzles (overhead, body & lower body)- MODEL GFS3FH
- OR**
- 1x Overhead ABS shower Rose - MODEL GFS1FH
- Manufactured to ANSI Z358.1-2009 specifications



Optional Extras		
Eyebath(on LHS)	Remote alarms	Alarm & Siren
Shower walk on Platform	Strainer	Eyebath foot treadle
Pendant Lamp	Flanged Inlets	Pressure reg.valve