



SAFETY SHOWERS & EYEBATHS

SHOWERS AND EYEBATHS SERVICES



GFTS 25L Tank shower



CH01

Manufactured from Glass Reinforced Plastic and Stainless Steel which are corrosion resistant materials, giving a long life, and suitability for outside use.
 Designed to be highly visible for ease of identification.
 These units are ideal for areas where there is no water supply; interrupted water supply; low water pressure to guarantee correct flow rate or a tepid water supply.
 Suitable for non hazardous or hazardous areas. ATEX or GOST certified.
 Electrical power requirement (If required) is 220-240v or 110-120v 1Ph 50-60Hz
 Suitable for temperatures -40 deg C to +50 deg C (on certain models)
 Available in Green, yellow or white. Green being standard.

KEY FEATURES

GUARANTEED 30 MINUTES OF TEPID WATER

- Green pre-insulated, sealed tank (2500 Litres)
- 2x 3/4" brass ball float valves & 6" plastic floats for quick filling
- Screened overflow (40mm)
- Screened vent
- 304 stainless frame, Linkages and fastenings
- Stainless valves
- Stainless panic bar operation (foot operation available as option)
- Stainless testing lever
- Removable lifting/positioning lugs
- Inspection hatches for maintenance purposes
- 1" BSPM inlet (other sized inlets available including flanged & NPT)
- Overhead ABS rose (75 LPM)
- Meets ANSI Z358.1-2009 standards
- Insulated lid
- All applicable Safety signs with green & white stripes

OTHER MODELS AVAILABLE

GFTS25L 316 - As above and manufactured from 316 stainless frame.

Optional Extras		
Water Heater pads & stat	Eyebath	Flexible eyewash
Various alarms (local & remote)	Alarm & Siren	Spring Loaded doors
Side & rear Panels	Lamps	Shower Foot Platform
Drain Sump(2" Outlet)	Strip Curtain	Temperature Gauge
water level indicator	Manual Drain valve	EB Foot treadle
Water Chiller	Sun Canopy	HCLENZ Kit
Drain Sump pump		



Picture shows optional extras fitted