



SAFETY SHOWERS & EYEBATHS



MODEL GFTSM



Self contained Tank shower suitable for Marine environments

Manufactured from Glass Reinforced Plastic and 316 Stainless Steel which are corrosion resistant materials, giving a long life, and suitability for outside use.

Designed to be highly visible for ease of identification.

Suitable for non hazardous or hazardous areas.

Suitable for temperatures -20 deg C to +40 deg C

Unit has been tested for horizontal load 0.61G and vertical load 0.44G.

KEY FEATURES

- Green 350L pre-insulated, sealed tank with internal baffles.
- 2x 3/4" brass ball float valves & 6" plastic floats suitable for 2-10Bar water supply pressure. (Low Pressure valves also available)
- Screened overflow (40mm) & vent for minimum risk of Legionella
- 316 stainless frame - Braced
- Lifting brackets
- Inspection hatch built in lid for maintenance purposes
- Stainless panic bar for extra security
- Stainless testing lever
- GRP walk on shower gritted platform operation(yellow)
- 1" BSPM inlet (other sized inlets available including flanged & NPT)
- Overhead ABS rose - 75lpm
- Meets ANSI Z358.1-2009 standards
- All applicable Safety signs with green & white stripes



Optional Extras		
Heater pad & stat	Eyebaths	Flexible eyewash
Various Alarms(local&remote)	Drain valve	PVC Curtain
Side & rear Panels	Lamps	Strip Curtain
Temperature Gauge	Drain Sump	Auto Siphon
water level indicator	Sirens	Sun Canopy

GFTSM shown with optional extras