



SAFETY SHOWERS & EYEBATHS

SHOWERS AND EYEBATHS SERVICES



ATANK12 - Remote header Tank



CH01

Manufactured from Glass Reinforced Plastic and Stainless Steel which are corrosion resistant materials, giving a long life, and suitability for outside use.
 Designed to be highly visible for ease of identification.
 These units are ideal for areas where there is no water supply; interrupted water supply; low water pressure to guarantee correct flow rate or a tepid water supply to another safety shower unit.
 Suitable for non hazardous or hazardous areas. ATEX, GOST & CSA Certified
 Electrical power requirement (If required) is 220-240v or 110-120v 1Ph 50-60Hz
 Suitable for temperatures -20 deg C to +40 deg C
 Available in Green, yellow or white. Green being standard.

KEY FEATURES

GUARANTEED 15 MINUTES OF TEPID WATER

- Green pre-insulated, sealed tank (12-1500 Litres)
- 2x 3/4" brass ball float valves & 6" plastic floats suitable for 2-10Bar water supply pressure. (Low Pressure valves also available)
- Screened overflow (40mm)
- Screened vent
- 304 stainless frame
- Removable lifting/positioning lugs
- Inspection hatch in lid for maintenance purposes
- 1" BSPM inlet (other sized inlets available including flanged & NPT)
- 2" BSPM outlet (other sized inlets available including flanged & NPT)
- Flow from header tank - (75 LPM)
- Meets ANSI Z358.1-2009 standards
- All applicable Safety signs with green & white stripes

OTHER MODELS AVAILABLE

ATANK12-CSA - As above but supplied with fa 1500litre fire retardant header tank

ATANK - As above but supplied with a 350litre header tank



Optional Extras		
Water Heater & stat	Lamp	Temperature Gauge
Water level indicator	Water Chiller	Sun Canopy
Water temperature alarm	Low water level alarm	Hclenz Kit
Submersible Pump		